

Productname : MOULDPRO MOULD RELEASE
Creationdate : 21.09.09
Ref.Nr.: UK10702-3-210909
Replaces:

1. IDENTIFICATION OF PRODUCT AND COMPANY

Productname : MOULDPRO MOULD RELEASE
Aerosol

Application : Release Agents

Company : MOULDPRO A/S
Baltorpbakken 10
DK-2750 Ballerup • Denmark
Phone: + 45 7020 3131
Fax: + 45 7020 3151
E-mail: info@mouldpro.com

In case of emergency :

2. HAZARD IDENTIFICATION

Health and Safety : Extremely Flammable
Irritating to skin.
Vapours may cause drowsiness and dizziness.

Environment : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Other hazards : Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.

3. COMPOSITION AND INFORMATION ON COMPONENTS

Hazardous ingredient	CAS-nr	EINECS	w/w %	symbol	R-phrases*	Notes
Naphtha (petroleum), hydrotreated light (benzene<0.1%)	64742-49-0	265-151-9	30-60	F,Xn,N	11-38-51/53-65-67	B,P
Hydrocarbons,C3-4-rich, petroleum	68512-91-4	270-990-9	30-60	F+	12	K

Productname : MOULDPRO MOULD RELEASE
Creationdate : 21.09.09
Ref.Nr.: UK10702-3-210909
Replaces:

Hazardous ingredient	CAS-nr	EINECS	w/w %	symbol	R-phrases*	Notes
distillate Petroleumgas (1,3-butadiene < 0.1%)						
Explanation notes						
B : substance with national established workplace exposure limit						
K : not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)						
P : not classified as carcinogen, less than 0.1% w/w benzene (Einecs-nr. 200-753-7)						

(* Explanation risk-phrases : see chapter 16)

Risk phrases in this section apply only to individual constituents and not to the finished preparation.

4. FIRST AID MEASURES

General Advice : The usual precautions for handling chemicals should be observed
If any symptoms should occur, seek medical advice.

Contact with eyes : If substance has got into eyes, immediately wash out with plenty of water

Contact with skin : Remove contaminated clothing immediately and drench affected skin with plenty of water. Then wash with soap and water
Seek medical advice

Inhalation : Fresh air, keep warm and at rest.

Ingestion : Ingestion is unlikely to occur
If swallowed accidentally, do not induce vomiting and seek medical advice.

5. FIRE-FIGHTING MEASURES

Flash point (without propellant): - 26 °C

Explosion limits : upper limit : 9.4 %
lower limit : 1.1 %

Extinguishing media : foam, carbon dioxide or dry agent

Fire-fighting procedures : Keep container(s) exposed to fire cool, by spraying with water

Unusual exposure hazard : Aerosols may explode if heated above 50°C

Productname :	MOULDPRO MOULD RELEASE	Creationdate :	21.09.09
Ref.Nr.:	UK10702-3-210909	Replaces:	

6. ACCIDENTAL RELEASE MEASURES

Personal precautions :	Shut off all ignition sources Ensure adequate ventilation
Environmental precautions :	Do not allow to enter public sewers and watercourses If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities
Cleaning methods :	Absorb spillage in suitable inert material

7. HANDLING AND STORAGE

Handling procedures :	Use only in well ventilated areas Do not pierce or burn aerosols, even after use. Do not spray on a naked flame or incandescent material. Do not breathe aerosols or vapours. Avoid contact with skin and eyes.
Storage procedures :	Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C. Keep in a cool, dry, well ventilated place Keep out of reach of children.

8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Control procedures :	Ensure adequate ventilation Keep away from heat and sources of ignition
Personal protection :	It is advisable to take precautions to avoid contact with skin and eyes when handling the product. Use only in well ventilated areas
inhalation :	In case of insufficient ventilation, wear suitable respiratory equipment.
hands and skin :	Wear suitable protective gloves (nitrile)
eyes :	Wear safety goggles.

9. PHYSICAL AND CHEMICAL PROPERTIES (for aerosols without propellant)

Apperance : physical state :	propane/butane propelled liquid
colour :	colourless to yellow
odour :	Odourless
Boiling point/range :	55 °C
Relative density :	0.718 g/cm ³ (@ 20°C)
pH :	not available

Productname :	MOULDPRO MOULD RELEASE	Creationdate :	21.09.09
Ref.Nr.:	UK10702-3-210909	Replaces:	

Vapour pressure :	not available
Relative vapour density :	not available
Solubility in water :	Insoluble in water
Flash point :	- 26 °C
Auto-ignition :	> 200 °C
Viscosity :	not available
Viscosity :	not available
Evaporation rate :	not available

10. STABILITY AND REACTIVITY

Conditions to be avoided :	Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat and sources of ignition No hazardous reactions known if used for its intended purpose
Materials to be avoided :	Strong oxidising agent
Hazardous decomposition compounds :	carbon oxides

11. TOXICOLOGICAL INFORMATION

Inhalation :	Inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion :	Ingestion is unlikely to occur After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.
Skin contact :	Irritating to skin
Eye contact :	Irritating to eyes
Other information:	No experimental data available

12. ECOLOGICAL INFORMATION

Other adverse effects :	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Do not allow to enter public sewers and watercourses If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities No experimental data available
--------------------------------	--

Productname :	MOULDPRO MOULD RELEASE	Creationdate :	21.09.09
Ref.Nr.:	UK10702-3-210909	Replaces:	

13. WASTE DISPOSAL

National regulations : Disposal should be in accordance with local, state or national legislation

14. TRANSPORT

UN-number :	1950
Road/Rail - ADR/RID :	UN1950 Aerosols Class : 2, PG : NA, Class code : 5F, Label : 2.1, Tunnel-code : (B/D)
Sea - IMDG :	UN1950 Aerosols Ltd Qty Class : 2.1, PG : NA, Label : 2.1
EmS	F-D,S-U
Air - IATA/CAO :	UN1950 Aerosols, flammable Class : 2.1, PG : NA, Label : RFG
Packing instr. LQ	Y203
PAX	203
CAO	203

15. REGULATORY INFORMATION

Warning symbol(s) :	F+ : EXTREMELY FLAMMABLE Xi : IRRITANT N : DANGEROUS FOR THE ENVIRONMENT
Risk-phrase(s) :	R12: Extremely flammable. R38: Irritating to skin. R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R67: Vapours may cause drowsiness and dizziness.
Safety-phrase(s) :	S2: Keep out of the reach of children. S16: Keep away from sources of ignition - No smoking. S23: Do not breathe vapours/spray. S24: Avoid contact with skin. S51: Use only in well-ventilated areas.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.
Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

Productname : MOULDPRO MOULD
RELEASE**Creationdate :** 21.09.09**Ref.Nr.:** UK10702-3-210909**Replaces:**

16. OTHER INFORMATION

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from Mouldpro

***Explanation risk-phrases:**

R11: Highly flammable.

R12: Extremely flammable.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R67: Vapours may cause drowsiness and dizziness.

This Material Safety Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Material Safety Data Sheet will be sent to you upon simple request or can be found on our website : www.mouldpro.com. We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.